

DS-XS8242-E/DW Free-standing Cabinet



- The Hikvision E-type server cabinet is compatible with 19 inch international standard floor standing glass door or perforated door cabinets. The cabinets are all made of high-quality cold-rolled sheet metal. Mainly used in data centers such as finance, securities, and data centers, it is specially designed for servers and can provide a high-performance and stable working environment for equipment in cabinets.

▪ Specification

Specifications	
Installation Method	Floor standing
Internal Space	42U
Static Load Capacity	1000KG
Dimensions (W*D*H) mm	800*1200*2050 (including casters)
Net Weight	112.3KG
Parameters	
Opening Percentage (Front Door)	78%
Opening Percentage (Rear Door)	78%
Front Door	1.2mm SPCC
Front and Rear Frame	1.2mm SPCC
Side Panel	1.2mm SPCC
Beam	1.5mm SPCC
Top Cover	1.2mm SPCC
Bottom panel	1.2mm SPCC
Vertical rail	2.0mm SPCC
Others	
Shelf	Optional: DS-XSPB12-E
Castor	4
Supporting leg	4
FAN	Optional: DS-XSFS12-E
PDU	Optional

▪ Available Model

DS-XS8242-E/DW

▪ Accessory

▪ Optional

DS-XSFS12-E	DS-XPUK06-Y/KYL	DS-XPEUR08-Y/KYL	DS-XSPB10-E
			

See Far, Go Further



www.hikvision.com
support@hikvision.com

